### **N351 Sportsman Cylinder Head**



## TRUE BLUE.

# **Real POWER Real PERFORMANCE Real SUBSTANCE**

#### Real VALUE

Ford Racing offers factory engineered parts for the Sportsman Circle Track Racer. The N351 cylinder head has been retooled and is now in stock and ready to ship. Designed for Ford engines in NASCAR Whelen Series, IMCA, WISSOTA, UARA, and most other stock car sanctioning groups on 351W engines. Developed by Ford Racing with the help of Robert Yates



Buzzy Adams – 2008 WISSOTA Modified Champion

- Long Brothers & Setzer NASCAR Late Model Stock
- Machined for 2.02" intake and 1.60" exhaust valve diameters
- Intake and exhaust valves have been moved .070" to unshroud the intake valve
- 10 degree valve angle to further improve air flow
- Thick deck and reinforced structure for improved sealing, increased section thickness in critical areas and webbed rocker bosses for improved strength.
- Designed for stud mount rocker arms.
- Compatible with Aftermarket and Ford Racing intakes



Cylinder head includes tracking date stamped in the machined surface on the end of the head





Ford Racing N351 Sportsman Cylinder Head		
Head part number	M-6049-N351	
Head material	Castiron	
Intake port location	Stock	
Intake port volume	200cc (+/- 2cc)	
Intake valve part number	M-6507-A351	
Intake Valve Head Diameter	2.02	
Intake valve length	5.120" Overall length	
Intake valve material	Stainless steel	
Intake valve stem diameter	11/32	
Intake guide material	Cast iron	
Intake valve seat material	Cast iron	
Exhaust port location	Custom	
Exhaust port volume	82cc (+/- 2cc)	
Exhaust valve part number	M-6505-A351	
Exhaust valve head diameter	1.6	
Exhaust valve length	5.130" Overall length	
Exhaust valve material	Stainless steel	
Exhaust valve stem diameter	11/32	
Exhaust valve guide material	Castiron	
Exhaust seat material	Castiron	
Combustion chamber volume	64.0 cc's	
Deck thickness	.400" (+/030)	
Rocker stud part number	M-6527-C311	
Pushrod guide plate part number	M-6566-D351	
Weight	51 lbs.	

#### **Recommended accessories**

Intake gasket	M-9439-A50	
Exhaust gasket	M-9448-A351	
Head gasket	M-6051-CP331	
Head bolts-studs	Check block applications	
Valve Covers	M-6582-E302P	
Spark plugs	.708" reach taper seat	

#### **Airflow**

Baseline Airflow data out of the box condition

- 2.02" intake valve M-6507-A351
- 1.60" exhaust valve M-6505-A351
- 4.060" Bore Clay radius approx. 1/2" intake side only

	Airflow - CFM - at	Airflow - CFM - at 28 inches of water	
Lift at valve - inches	Intake	Exhaust	
0.100"	67.6	54.2	
0.200"	141.5	104.1	
0.300"	193.8	131.4	
0.400"	213.2	147.1	
0.500"	228.0	157.2	
0.600"	241.1	165.7	